







## BRAKE PARTS

*Anchor Pin Spider Bushings, Locks,  
Lock Rings & Retainers*

### ANCHOR PIN SPIDER BUSHINGS






	PART NO.	REPLACES	O.D.	I.D.	L.G.	APPLICATION AND GENERAL INFORMATION
	<b>03.3052.0</b>	Rockwell 1225-B-496 and Trailmobile 15409	1-3/8" = 34.9mm	1-1/4" = 31.8mm	1-15/32" = 37.3mm	Split, Stainless Steel, General Purpose Bushing Use with 03.3203.0 Anchor Pin
	<b>03.3053.0</b>	Eaton B-2022	1-3/8" = 34.9mm	1-1/4" = 31.8mm	1-7/16" = 36.5mm	Tab Jointed, Steel-Backed Bronze General Purpose Bushing
	<b>03.3058.0</b>	Rockwell 1225-G-449	1-3/8" = 34.9mm	1-1/4" = 31.8mm	1-15/32" = 37.3mm	Split, Stainless steel bushing with slot on center for Rockwell Truck Brakes. Use with 03.3232.0 and 03.3352.0 Anchor Pins
	<b>03.3059.0</b>	Rockwell	1-3/8" = 34.9mm	1-1/4" = 31.8mm	1-7/16" = 36.5mm	Tab Jointed, Steel-Backed Bronze, Bushing with Slot on Centre for Rockwell Truck Brakes

### ANCHOR PIN – LOCKS, LOCK RINGS AND RETAINERS

	PART NO.	REPLACES	O.D.	I.D.	L.G.	APPLICATION AND GENERAL INFORMATION
<b>ANCHOR PIN WASHER</b> 	<b>03.3103.0</b>	Rockwell 1229-B-1848	1-7/8" = 47.6mm	1-1/4" = 31.8mm	1-1/16" = 27.0mm	Plated Steel General Purpose Washer Use with 03.3203.0 Anchor Pin
	<b>03.3164.0</b>	Spicer M10HM136 and Std. Forge 403147	1-1/2" = 38.1mm	1" = 25.4mm	1/32" = 0.8mm	Plated Steel Washer for Std. Forge 12-1/4" Dia. Brakes Use with 03.3246.0 Anchor Pin
<b>ANCHOR PIN CIRCLIP</b> 	<b>03.3121.0</b>	Eaton B-1214 & 820007, Rockwell 1229-X-1116, Spicer 31624 and Std. Forge 214108	<b>SUITS SHAFT</b> 1-1/4" = 31.8mm	<b>WIDTH</b> 0.050" = 1.27mm		Can be used on all 1-1/4" Anchor Pins with Circlip Grooves Same as Part No. 03.2601.0
	<b>03.3163.0</b>	Freighter 152-06206 Spicer M1 OHR1 04 and Std. Forge 214107	1" = 25.4mm	0.042" = 10.7mm		For Std. Forge 12-1/4" Dia. Brakes (Suits 1" Anchor Pin)

## BRAKE PARTS

*Anchor Pin Spider Bushings, Locks,  
Lock Rings & Retainers*

	PART NO.	REPLACES	O.D.	I.D.	L.G.	APPLICATION AND GENERAL INFORMATION
ANCHOR PIN SPRING WASHER 	70.103.12	-	O.D.	I.D.	THICK	Use with 03.3240.0, 03.3241.0, 03.3242.0 and 03.3243.0 Anchor Pins
			1-15/64" = 31.4mm	3/4" = 19.1mm	3/16" = 4.8mm	
ANCHOR PIN "C" WASHER 	03.3153.0	Dana 12061, Kershaw 11526, Rockwell 1229-M-221, Spicer M10HN154 and Std. Forge 403104			2.0mm	For Dana and Std. Forge 12-1/4" Dia. Trailer Brakes For Rockwell 16-1/4" "T" Series Steering Axle Brake Plated Steel "C" Washer Suits 1" Shaft
ANCHOR PIN LINK 	03.3161.0	Kershaw 11526, Spicer M1 OHR1 01 and Std. Forge 999100	3-5/8" (92.1 mm) OAL. 1-15/16" (49.2mm) Centre to Centre  7/8" (22.2mm) Hole Dia. 1/4" (6.4mm) Thick			For Early Model Std. Forge 12-1/4" Dia. Brakes with Cast Shoes For Dana 12-1/4" Dia. Brakes For Prolog Brakes
ANCHOR PIN JAM NUT 	03.3172.0	Kershaw 12052, Spicer 500371-8, Std. Forge 402101 and Trailmobile 3-23-2	3/4"-16	1-1/8" = 28.6mm	27/64" = 10.7mm	Plated Steel Nut Std. Forge and Dana 12-1/4" Dia. Brakes Use with 03.3240.0, 03.3241.0, 03.3242.0 and 03.3243.0 Anchor Pins
ANCHOR PIN END WASHER 	03.3175.0	-	O.D	I.D	THICK	Plated Steel General Purpose End Washer Use 2 per Bolt-On Anchor Pin