











S-CAM (CAMSHAFT) BUSHINGS

	PART NO.	O.D.	I.D	LENGTH	APPLICATION AND GENERAL
NYLON BUSH 	03.2101.0	2-3/4" = 69.9mm	1-1/2" = 38.1mm	2-1/2" = 63.5mm	For Rockwell, (Freighter MK VA, Fruehauf Round & I Beam, Early Haulmark, MCgrath, and PBR); Spline-end Bushing Includes: 2 'O' Rings 03.2451.0 and 1 Grease Nipple Replaces: Fruehauf 515148 and Rockwell A-3299-G-1541
NYLON BUSH 	03.2102.0	2-7/8" = 73.0mm	1-19/32" = 40.5mm	2-1/2" = 63.5mm	For Fruehauf "Pro-Par" with Early Style Bracket; Spline-End Bushing Includes: 2 'O' Rings 03.2452.0 and 1 Grease Nipple Replaces: Fruehauf AXA-0429-900
NYLON BUSH 	03.2103.0	2-1/2" = 63.5mm	1-19/32" = 40.5mm	1-1/2" = 38.1mm	For Fruehauf "Pro-Par" with Late Style Bracket; Spline-End Bushing Includes: 2 'O' Rings 03.2452.0 and 1 Grease Nipple Replaces: Fruehauf ACD-2285-900
NYLON BUSH 	03.2107.0	2-15/32" = 62.7mm	1-1/2" = 38.1mm	1-3/4" = 44.5mm	For Fruehauf "Pro-Par" with Late Style Bracket; Spline-End Bushing Includes: 2 'O' Rings 03.2451.0 and 1 Grease Nipple Replaces: Std Forge 405128 & 405999-001
	03.2109.0	2-1/8" = 54.0mm	1-1/2" = 38.1mm	1" = 25.4mm	For Rockwell with Late Outer Bracket, (Freighter RN, TN, ARN&ATN); Spline-End Bushing Nylon Bush Use with 2 'O' Rings 03.2453.0 Replaces: Freighter 154-00835 and Rockwell 1125-P-640







BRAKE PARTS

S-Cam Bushings

	PART NO.	O.D.	I.D	LENGTH	APPLICATION AND GENERAL
	03.2110.0	2-15/32" = 62.7mm	1-1/2" = 38.1mm	1-1/2" = 38.1mm	For Dana AND Kershaw with Adjustable Outer Bracket; Spline-End Bushing Includes: 1 Grease Nipple Use with 2 'O' Rings 03.2453.0 Replaces: Dana 10055 & 16064, Kershaw 11109 and Spicer M10WJ100
	03.2119.5	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1.77" = 45.0mm	For Eaton, Mack, and Rockwell Front and Drive Axles; Spline-End Bushing Plated Steel Bush Used in Support Bracket for Mack Fitted with Tayco Brakes Includes: 1 'O' Ring 03.2455.0
	03.2200.5	1-7/8" = 47.6mm	1-1/2" = 38.1mm	2" = 50.8mm	For Rockwell, (Freighter MK VA, Fruehauf Round & I Beam, Early Haulmark, MCgrath, and PBR); Spider Bushing Includes: 2 'O' Rings 03.2455.0 and 1 Lock Ring 03.2330.0
	03.2201.0	1-7/8" = 47.6mm	1-1/2" = 38.1mm	7/8" = 22.2mm	For Rockwell, (Freighter MK VA, Fruehauf Round & I Beam, Early Haulmark, MCgrath, and PBR); Spider Bushing (white bush only) Includes: 1 'O' Ring 03.2454.0 and 1 'O' Ring 03.2455.0 Used: On Cam Head Side of Spider Only Replaces: Freighter 154-00471, Fruehauf ACA-3266 and Rockwell A-1225-D-420
	03.2202.0	1-7/8" = 47.6mm	1-1/2" = 38.1mm	7/8" = 22.2mm	For Rockwell, (Freighter MK VA, Fruehauf Round & I Beam, Early Haulmark, MCgrath, and PBR); Spider Bushing (yellow bush only) Includes: 1 'O' Ring 03.2454.0 and 1 'O' Ring 03.2455.0 Used: On Spline-End Side of Spider Only Replaces: Freighter 154-00472, Fruehauf ACA-3265 and Rockwell A-1225-V-438







BRAKE PARTS

S-Cam Bushings

	PART NO.	O.D.	I.D	LENGTH	APPLICATION AND GENERAL
	03.2203.0	2" = 50.8mm	1-5/8" = 41.3mm	7/8" = 22.2mm	For Fruehauf "Pro-Par" Axle; Spider Bushing Nylon Bush (White) Includes: 1 'O' Ring 03.2456.0 and 1 'O' Ring 03.2457.0 Use two bushes per Spider Replaces: Fruehauf AXA-0413-900
	03.2203.5	2" = 50.8mm	1-5/8" = 41.3mm	2" = 50.8mm	For Fruehauf "Pro-Par" Axle; Spider Bushing Plated Steel Version of 03.2203.0 Includes: 2 'O' Rings 03.2457.0 and 1 Lock Ring 03.2333.0
	03.2204.0	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-1/2" = 38.1mm	For Dana, Rockwell, (Freighter TN), and Std. Forge; Spline-End and Spider Bushing Nylon Bush Use with 2 Seals 03.2402.0 (to give 1-7/8" Overall LG) or 2 Seals 03.2403.0 (to give 2" Overall LG) Replaces: Freightor 154-00834, Spicer M1 OWJ118 and Std. Forge 405129
	03.2204.3	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-1/2" = 38.1mm	For Dana, Rockwell, (Freighter TN), and Std. Forge; Spline-End and Spider Bushing Plated Steel Version of 03.2204.0 Use with 2 Seals 03.2402.0 (to give 1-7/8" Overall LG) or 2 Seals 03.2403.0 (to give 2" Overall LG)
	03.2204.4	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-7/8" = 47.6mm	For Dana, Rockwell, (Freighter TN), and Std. Forge; Spline-End and Spider Bushing Plated Steel, 'O' Ring 1-7/8", Version of 03.2204.0 Includes: 2 'O' Rings 03.2455.0
	03.2204.5	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-15/16" = 49.2mm	For Dana, Rockwell, (Freighter TN), and Std. Forge; Spline-End and Spider Bushing Plated "Flanged" Steel 1-7/8", 'O' Ring, Version of 03.2204.0 Includes: 2 'O' Rings 03.2455.0








BRAKE PARTS

S-Cam Bushings

	PART NO.	O.D.	I.D	LENGTH	APPLICATION AND GENERAL
	03.2204.7	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-1/2" = 38.1mm	For Dana, Rockwell, (Freighter TN), and Std. Forge; Spline-End and Spider Bushing Sintered Bronze Version of 03.2204.0 Use with 2 Seals 03.2402.0 (to give 1-7/8" Overall LG) or 2 Seals 03.2403.0 (to give 2" Overall LG)
	03.2204.8	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-7/8" = 47.6mm	For Dana, Rockwell, (Freighter TN), and Std. Forge; Spline-End and Spider Bushing Sintered Bronze 1-7/8", 'O' Ring, Version of 03.2204.0 Includes: 2 'O' Rings 03.2455.0
	03.2206.4	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-1/2" = 38.1mm	For Rockwell RL,RN&RQ Pre-121, (Freighter RN); Spider Bushing Plated Steel, 'O' Ring, Version of Outer 03.2205.0 and Inner 03.2206.0 Includes: 2 'O' Rings 03.2455.0
	03.2206.5	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-9/16" = 39.7mm	For Rockwell RL,RN&RQ Pre-121, (Freighter RN); Spider Bushing Plated "Flanged" Steel, 'O' Ring, Version of Outer 03.2205.0 and Inner 03.2206.0 Includes: 2 'O' Rings 03.2455.0
	03.2206.8	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-1/2" = 38.1mm	For Rockwell RL,RN&RQ Pre-121, (Freighter RN); Spider Bushing Sintered Bronze, 'O' Ring, Version of Outer 03.2205.0 and Inner 03.2206.0 Includes: 2 'O' Rings 03.2455.0
	03.2207.0	2" = 50.8mm	1-7/8" = 47.6mm	1-5/16" = 33.3mm	For Rockwell 4000 & 6000 Series, (Freighter ARN & ATN); Outer Spider Bushing Use with Inner Spider Bush 03.2208.0, 1 Seal 03.2405.0, and 1 'O' Ring 03.2452.0 Replaces: Freighter 154-00897 and Rockwell 1225-A-833







BRAKE PARTS

S-Cam Bushings

	PART NO.	O.D.	I.D.	LENGTH	APPLICATION AND GENERAL
	03.2208.0	1-7/8" = 47.6mm	1-5/8" = 41.3mm	1-1/8" = 28.6mm	For Rockwell 4000 & 6000 Series, (Freighter ARN & ATN); Inner Spider Bushing Use with Outer Spider Bush 03.2207.0, 1 Seal 03.2405.0, and 1 'O' Ring 03.2452.0 Replaces: Freighter 154-00896 and Rockwell 1225-B-834
	03.2208.4	2" = 50.8mm	1-5/8" = 41.3mm	1-1/2" = 38.1mm	For Rockwell 4000 & 6000 Series, (Freighter ARN & ATN); Spider Bushing Plated Steel, 'O' Ring, Version of Outer 03.2207.0 and Inner 03.2208.0 Includes: 2 'O' Rings 03.2457.0
	03.2208.5	2" = 50.8mm	1-5/8" = 41.3mm	1-9/16" = 39.7mm	For Rockwell 4000 & 6000 Series, (Freighter ARN & ATN); Spider Bushing Plated "Flanged" Steel, 'O' Ring, Version of Outer 03.2207.0 and Inner 03.2208.0 Includes: 2 'O' Rings 03.2457.0
	03.2208.8	2" = 50.8mm	1-5/8" = 41.3mm	1-1/2" = 38.1mm	For Rockwell 4000 & 6000 Series, (Freighter ARN & ATN); Spider Bushing Sintered Bronze, 'O' Ring, Version of Outer 03.2207.0 and Inner 03.2208.0 Includes: 2 'O' Rings 03.2457.0
	03.2209.0	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-3/16" = 30.2mm	For Eaton, Mack, and Rockwell Front and Drive Axles; Spline-End and Cam Head End Bushing Nylon Bush (No Grease Hole) Use with 1 Seal that is appropriate for Application Replaces: Rockwell 1225-N-378
	03.2209.2	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-31/64" = 37.7mm	For Eaton, Mack, and Rockwell Front and Drive Axles; Spline-End and Cam Head End Bushing Nylon "Flanged" Version of 03.2209.0 Includes: 1 'O' Ring 03.2455.0
	03.2209.3	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1-3/16" = 30.2mm	For Eaton, Mack, and Rockwell Front and Drive Axles; Spline-End and Cam Head End Bushing Plated Steel Version of 03.2209.0. Use with 1 Seal appropriate for Application.






BRAKE PARTS

S-Cam Bushings

	PART NO.	O.D.	I.D	LENGTH	APPLICATION AND GENERAL
	03.2209.5	1-7/8" = 47.6mm	1-1/2" = 38.1mm	39mm	For Eaton, Mack, and Rockwell Front and Drive Axles; Spline-End and Cam Head End Bushing Plated "Flanged" Steel Version of 03.2209.0 Used in Spider for Mack Fitted with Tayco Brakes Includes: 1 'O' Ring 03.2455.0
	03.2210.0	1-7/8" = 47.6mm	1-1/4" = 31.8mm	1-3/16" = 30.2mm	For Rockwell 15" DIA. 'T' Series Front; Spline-End and Cam Head End Bushing Replaces: Rockwell 1225-M-897 Use with 1 Seal 03.2401.0 for Spline-End Use with 1 Seal 03.2425.0 for Cam Head End
	03.2214.3	1-7/8" = 47.6mm	1-1/2" = 38.1mm	2" = 50.8mm	For Dana and Std. Forge Trailer Axle; Spline-End and Spider Bushing Plated Steel Version of 03.2214.0 Use with 2 Seals 03.2402.0
	03.2214.4	1-7/8" = 47.6mm	1-1/2" = 38.1mm	2-3/8" = 60.3mm	For Dana and Std. Forge Trailer Axle; Spline-End and Spider Bushing Plated Steel Version of 03.2214.0 Includes: 2 'O' Rings 03.2455.0
	03.2214.7	1-7/8" = 47.6mm	1-1/2" = 38.1mm	2" = 50.8mm	For Dana and Std. Forge Trailer Axle; Spline-End and Spider Bushing Sintered Bronze Version of 03.2214.0 Use with 2 Seals 03.2402.0
	03.2214.8	1-7/8" = 47.6mm	1-1/2" = 38.1mm	2" = 50.8mm	For Dana and Std. Forge Trailer Axle; Spline-End and Spider Bushing Sintered Bronze Version of 03.2214.0 Includes: 2 'O' Rings 03.2455.0

BRAKE PARTS

S-Cam Bushings

	PART NO.	O.D.	I.D	LENGTH	APPLICATION AND GENERAL
	03.2233.5	2" = 50.8mm	1-1/2" = 38.1mm	2" = 50.8mm	Converts Fruehauf "Pro-Par" Spider to Suit 1-1/2" Dia. Camshaft Includes: 2 'O' Rings 03.2455.0 and 1 Lockring 03.2333.0
	03.2238.5	2" = 50.8mm	1-1/2" = 38.1mm	1-9/16" = 39.7mm	Converts Rockwell 4000 & 6000 Series, (Freighter ARN & ATN), Spider to Suit 1-1/2" Dia. Camshaft Includes: 2 'O' Rings 03.2455.0
	03.2271.4	2" = 50.8mm	1-1/2" = 38.1mm	2" = 50.8mm	For Pantha Includes: 2 'O' Rings 03.2455.0
	03.2330.0		1-7/8" = 47.6mm		Lock Ring Only Suits: Camshaft Bush 03.2200.2, 03.2200.5 and 03.2200.9
	03.2333.0		2" = 50.8mm		Lock Ring Only Suits: Camshaft Bush 03.2203.2, 03.2203.5 and 03.2203.9