



S-CAM (CAMSHAFT) SEALS

	PART NO.	REPLACES	O.D.	SUITS SHAFT	THICK	APPLICATION
	03.2402.0	Rockwell 1205-M-II05, Spicer M16HH100 and Std. Forge 408101	1-7/8" = 47.6mm	1-1/2" = 38.1mm	3/16" = 4.8mm	Late Model Rockwell, Std. Forge Weld-on Spiders, and Dana Cam Seal (1-1/2" Dia. Cam)
	03.2403.0	Eaton B-1736-1, 40864 & 77903	1-7/8" = 47.6mm	1-1/2" = 38.1mm	1/4" = 6.4mm	Eaton Cam Seal (1-1/2" Dia. Cam)
	03.2404.0	Rockwell 1705-M-143 and Eaton B-1662 & 820064	2-1/16" = 52.4mm	1-1/2" = 38.1mm	1/4" = 6.4mm	Rockwell, Std. Forge and Eaton Cam Seal (1-1/2" Dia. Cam)
	03.2405.0	Rockwell 1205-U-1451	2" = 50.8mm	1-5/8" = 41.3mm	3/16" = 4.8mm	Rockwell "4000-6000" Series Axles Cam Seal (1-5/8" Dia. Cam)

CAMSHAFT 'O' RINGS

	PART NO.	REPLACES	SUITS SHAFTS	I.D.	WIDTH	APPLICATION AND GENERAL INFORMATION
	03.2452.0	Fruehauf AXA-0412-1	1-5/8" = 41.3mm	1.609" = 40.9mm	0.139" = 3.5mm	Suits Bushing: 03.2102.0 & 03.2103.0
	03.2455.0	Rockwell 1205-R-746	1-1/2" = 38.1mm	1.487" = 37.8mm	0.103" = 2.6mm	Suits Bushing: 03.2119.5, 03.2200.2, 03.2200.5, 03.2200.9, 03.2201.0, 03.2202.0, 03.2204.4, 03.2204.5, 03.2204.8, 03.2206.4, 03.2206.5, 03.2206.8, 03.2209.2, 03.2209.4, 03.2209.5, 03.2209.9, 03.2214.4, 03.2233.5, & 03.2271.4 (Inside)
	03.2457.0	Fruehauf AXA-0414-1	1-5/8" = 41.3mm	1.612" = 40.9mm	0.103" = 2.6mm	Suits Bushing: 03.2203.0, 03.2203.2, 03.2203.5, 03.2203.9, 03.2208.4, 03.2208.5 & 03.2208.8 (Inside)