









TURN-TABLE PARTS (Fifth Wheel Parts)
Lube Pads, King Pins, Speed Nuts & Screws



LUBE PADS, KING PINS, SPEED NUTS & SCREWS

	PART NO.	DIMENSIONS	APPLICATION AND GENERAL INFORMATION
<p>RECTANGULAR LUBE PAD – COUNTER SUNK</p> 	20.7101.0	<p>1010mm Length</p> <p>940mm Wide</p> <p>75mm I.D.</p> <p>4.5mm Thick</p>	<p>Secure Lube Pad to semi-trailer skid plate using 20.7102.0 Screws. Use of a Lube Pad reduces turntable wear and eliminates the need for grease.</p>
<p>SCREW PACK</p> 	20.7102.0	<p>5/16" BSW Thread</p> <p>19.1 mm = 3/4" Length</p>	<p>Use with Lube Pads 20.7101.0 and 20.7103.0</p> <p>16 Screws per Pack</p>
<p>UNDRILLED – 3-1/2" KINGPIN</p> 	20.7103.0	<p>1010mm Length</p> <p>940mm Wide</p> <p>114mm I.D.</p> <p>4.5mm Thick</p>	<p>Drill lube pad to suit.</p> <p>Secure Lube Pad to semi-trailer skid plate using 20.7102.0 Screws. Use of a Lube Pad reduces turntable wear and eliminates the need for grease.</p>
<p>UNDRILLED – 2" KINGPIN</p> 	20.7104.0	<p>1010mm Length</p> <p>940mm Wide</p> <p>114mm I.D.</p> <p>4.5mm Thick</p>	<p>Drill lube pad to suit.</p> <p>Secure Lube Pad to semi-trailer skid plate using 20.7102.0 Screws. Use of a Lube Pad reduces turntable wear and eliminates the need for grease.</p>

TURN-TABLE PARTS (Fifth Wheel Parts)
Lube Pads, King Pins, Speed Nuts & Screws

	PART NO.	DIMENSIONS	APPLICATION AND GENERAL INFORMATION
<p>ROUND LUBE PAD – RECESSED</p> 	20.7105.0	<p>910mm O.D. 135mm Recess Dia. 75mm I.D. 4.5mm Thick</p>	Secure Lube Pad to semi-trailer skid plate using 20.7106.0 Speed Nut. Use of a Lube Pad reduces turntable wear and eliminates the need for grease.
LUBE PAD + SPEED NUT	20.7105.08		Kit includes Round Lube Pad Recessed and Speed Nut. Part Numbers: 20.7105.0 + 20.7106.0
<p>SPEED NUT</p> 	20.7106.0	<p>124.0mm O.D. 72.5mm I.D.</p>	<p>Secures Lube Pad to Skid Plate Use with Lube Pad 20.7105.0</p>
<p>ROUND LUBE PAD – RECESSED</p> 	20.7108.0	<p>910mm O.D. 172mm Recess Dia. 114mm I.D. 4.5mm Thick</p>	Secure Lube Pad to semi-trailer skid plate using 20.7109.0 Speed Nut. Use of a Lube Pad reduces turntable wear and eliminates the need for grease.
LUBE PAD + SPEED NUT	20.7108.08		Kit includes Round Lube Pad Recessed and Speed Nut. Part Numbers 20.7108.0 + 20.7109.0
<p>SPEED NUT</p> 	20.7109.0	<p>164.0mm O.D. 113.5mm I.D.</p>	<p>Secures Lube Pad to Skid Plate Use with Lube Pad 20.7108.0 & 20.7110.0</p>

TURN-TABLE PARTS (Fifth Wheel Parts)
Lube Pads, King Pins, Speed Nuts & Screws

	PART NO.	DIMENSIONS	APPLICATION AND GENERAL INFORMATION
<p>ROUND LUBE PAD – RECESSED</p> 	20.7110.0	<p>1300mm O.D. 172mm Recess Dia. 114mm I.D. 4.5mm Thick</p>	<p>For Boomerang</p> <p>Secure Lube Pad to semi-trailer skid plate using 20.7109.0 Speed Nut. Use of a Lube Pad reduces turntable wear and eliminates the need for grease.</p>
<p>LUBE PAD + SPEED NUT</p>	20.7110.08		<p>Kit includes Round Lube Pad Recessed and Speed Nut. Part Numbers 20.7110.0 + 20.7109.0</p>
<p>ROUND LUBE PAD – UNRECESSED</p> 	20.7115.0	<p>1300mm O.D. 114mm I.D. 4.5mm Thick</p>	<p>For Boomerang</p> <p>Use of a Lube Pad reduces turntable wear and eliminates the need for grease.</p>